

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016
Version: 3

Language: en-CA,US

Date of print: 19/12/2016
Page: 1 of 12

1. Product and company identification

Product identifier

Trade name: Non-Woven Abrasives
This safety data sheet pertains to the following products:
POLINOX® unmounted flap wheels
POLINOX® cross buffs
POLINOX® mounted flap wheels
POLINOX® unitized wheels
POLINOX® unitized discs
POLINOX® convolute wheels
POLINOX® spindle mount discs
POLINOX® hand pads
POLINOX® marbling discs
POLINOX® finishing drums
POLIVLIES® surface conditioning belts
POLIVLIES® surface conditioning hook & loop discs
POLIVLIES® flap disc
POLICLEAN® discs
POLICLEAN® mounted wheels
COMBIDISC® POLICLEAN® discs
COMBIDISC® surface conditioning discs
COMBIDISC® finishing discs
COMBIDISC® unitized discs
COMBICLICK® surface conditioning discs
COMBICLICK® finishing discs
COMBICLICK® unitized discs
Non Woven Shop Rolls

Relevant identified uses of the substance or mixture and uses advised against

General use: Grinding and sanding of different kinds of materials.
For industrial purposes only

Details of the supplier of the safety data sheet

Company name:	PFERD INC.	PFERD CANADA INC.
Street/POB-No.:	9201 W. Heather Ave.	Street/POB-No.: 5570 McAdam Road
Postal Code, city:	Milwaukee, WI 53224, USA	Postal Code, city: Mississauga, Ontario L4Z 1P1, Canada
WWW:	www.pferdusa.com	WWW: www.pferdusa.com
E-mail:	sales@pferdusa.com	E-mail: sales@pferdcanada.ca
Telephone:	262-509-5614	Telephone: (905) 501-1555
Telefax:	262-255-2840	Telefax: (905) 501-1554
Dept. responsible for information:	1-800-342-9015	Dept. responsible for information: 1-866-245-1555

Emergency phone number

USA/Canada: 1-800-255-3924

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016
Version: 3

Language: en-CA,US

Date of print: 19/12/2016
Page: 2 of 12

2. Hazards identification

Emergency overview

Appearance: Form: solid
Color: varying colors
Odor: No data available
Classification: Article not subject to hazard labeling or classification.

Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Mechanical processing can produce particles and dust.
Inhalation of dust may cause irritation of the respiratory system.
Fibers and dust: Skin irritation, mucous membrane irritation, eye irritations.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Non-woven abrasives

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016
Version: 3

Language: en-CA,US

Date of print: 19/12/2016
Page: 3 of 12

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS -	Nylon fibre	< 80 %	not applicable
CAS 1344-28-1	Aluminium oxide	< 70 %	not applicable
CAS 409-21-2	Silicon carbide	< 70 %	not applicable
CAS -	synthetic resin, polymerized	< 60 %	not applicable
CAS -	Cotton-Polyester-cloth	< 40 %	not applicable
CAS -	Polyester cloth	< 40 %	not applicable
CAS -	Cotton cloth	< 40 %	not applicable
CAS 65997-17-3	Fibre glass weaves	< 30 %	not applicable
CAS 471-34-1	Calcium carbonate	< 5 %	not applicable
CAS 13983-17-0	Wollastonite	< 5 %	not applicable
CAS -	Aluminium Silicates	< 5 %	not applicable
CAS 13463-67-7	Titanium dioxide	< 3 %	Carcinogenicity 2.
CAS 7631-86-9	Silicon dioxide	< 2 %	not applicable
CAS -	paper	< 2 %	not applicable
CAS 26761-40-0	Diisodecylphthalate	< 1.5 %	not applicable
CAS 9002-86-2	Polyvinyl chloride	< 1.5 %	not applicable
CAS 1309-37-1	Diiron trioxide	< 1.5 %	not applicable
CAS 8042-47-5	White mineral oil (petroleum)	< 1 %	not applicable
CAS -	Pigments	< 1 %	not applicable
CAS 64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	< 0.2 %	not applicable
CAS 14808-60-7	Quartz (SiO ₂)	< 0.15 %	Carcinogenicity 1A.

Additional information: The ingredients are embedded in the product.

4. First aid measures

In case of inhalation: Fibers/dusts: Provide fresh air. If you feel unwell, seek medical advice.

Following skin contact: Fibers/dusts: Remove residues with soap and water. In case of skin reactions, consult a physician.

After eye contact: Fibers/dusts: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if any. In case of eye irritation consult an ophthalmologist.

After swallowing: Fibers/dusts: Rinse mouth with water. Give water to drink in small sips. If you feel unwell, seek medical advice.

Most important symptoms and effects, both acute and delayed

Fibers/dusts: Can cause skin, eye and respiratory tract irritation.

Information to physician

Treat symptomatically.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016

Version: 3

Language: en-CA,US

Date of print: 19/12/2016

Page: 4 of 12

5. Fire fighting measures

Flash point/flash point range:

No data available

Auto-ignition temperature: No data available

Suitable extinguishing media:

Product is non-combustible. Extinguishing materials should therefore be selected according to surroundings.

Specific hazards arising from the chemical

At temperatures above 482 °F (250 °C) hazardous decomposition products may be generated.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information: Do not allow fire water to penetrate into surface or ground water.

6. Accidental release measures

Personal precautions:

Avoid generation of dust. Do not inhale substance.
In case of heating: development of gas/vapor possible.
Provide adequate ventilation. Wear appropriate protective equipment.
Avoid contact with the substance. Keep unprotected people away.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Methods for clean-up:

Take up mechanically, placing in appropriate containers for disposal.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Avoid generation of dust.
In case of heating: development of gas/vapor possible.
Do not inhale substance. Wear appropriate protective equipment. Avoid contact with the substance.

Storage

Requirements for storerooms and containers:

Keep container tightly closed and dry.
Protect from heat and direct sunlight.

Hints on joint storage:

Do not store together with oxidizing agents or acids.
Do not store together with food.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016
Version: 3

Language: en-CA,US

Date of print: 19/12/2016
Page: 5 of 12

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
1344-28-1	Aluminium oxide	Canada, Alberta: OEL 8 hour	10 mg/m ³
		Canada, Québec: VEMP	10 mg/m ³ (inhalable fraction)
		USA: OSHA: TWA	15 mg/m ³ inhalable fraction
		USA: OSHA: TWA	5 mg/m ³ (respirable fraction)
409-21-2	Silicon carbide	Canada, Alberta: OEL 8 hour	0.1 fibers/cm ³ (fibrous, including whiskers; inhalable fraction)
		Canada, Alberta: OEL 8 hour	10 mg/m ³ (non-fibrous; inhalable fraction)
		Canada, Alberta: OEL 8 hour	3 mg/m ³ (non-fibrous; respirable fraction)
		Canada, BC: OEL TWA	0.1 fibers/cm ³ (fibrous, including whiskers)
		Canada, BC: OEL TWA	10 mg/m ³ (non-fibrous; inhalable fraction)
		Canada, BC: OEL TWA	3 mg/m ³ (non-fibrous; respirable fraction)
		Canada, Ontario: OEL TWA	0.1 fibers/cm ³ (fibrous, including whiskers; inhalable fraction)
		Canada, Ontario: OEL TWA	10 mg/m ³ (non-fibrous; inhalable fraction)
		Canada, Ontario: OEL TWA	3 mg/m ³ (non-fibrous; respirable fraction)
		Canada, Québec: VEMP	10 mg/m ³ (non-fibrous; inhalable fraction)
		USA: ACGIH: TWA	0.1 fibers/cm ³ (fibrous, including whiskers)
		USA: ACGIH: TWA	10 mg/m ³ (inhalable fraction; particulate matter containing no asbestos and < 1% crystalline silica)
		USA: ACGIH: TWA	3 mg/m ³ (respirable fraction; particulate matter containing no asbestos and < 1% crystalline silica)
		USA: NIOSH: TWA	10 mg/m ³ inhalable fraction
USA: NIOSH: TWA	5 mg/m ³ (respirable fraction)		
USA: OSHA: TWA	15 mg/m ³ inhalable fraction		
USA: OSHA: TWA	5 mg/m ³ (respirable fraction)		

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016

Version: 3

Language: en-CA,US

Date of print: 19/12/2016

Page: 6 of 12

CAS No.	Designation	Type	Limit value
65997-17-3	Fibre glass weaves	Canada, Alberta: OEL 8 hour	1 fibers/cm ³ Glass Fibres, Continuous filament
		Canada, Alberta: OEL 8 hour	5 mg/m ³ Glass Fibres, continuous filament, glass wool, inhalable fraction
		Canada, BC: OEL TWA	1 fibers/cm ³ Synthetic Vitreous Fibres - Continuous filament glass fibres
		Canada, BC: OEL TWA	5 mg/m ³ Synthetic Vitreous Fibres - Continuous filament glass fibres; inhalable fraction
		Canada, Ontario: OEL TWA	1 fibers/cm ³ Synthetic Vitreous Fibres, Continuous filament glass fibres
		Canada, Ontario: OEL TWA	5 mg/m ³ Synthetic Vitreous Fibres (Man Made Mineral Fibres), Continuous filament glass fibres
		Canada, Québec: VEMP	10 mg/m ³ Fibre de verre en filament continu; Pt note 1
		USA: ACGIH: TWA	1 fibers/cm ³ Synthetic vitreous fibres, Continuous filament glass fibres
		USA: ACGIH: TWA	5 mg/m ³ Synthetic vitreous fibres, Continuous filament glass fibres; inhalable fraction
		USA: NIOSH: TWA	3 fibers/cm ³ Fibers less than or equal to 3,5 µm in diameter and greater than or equal to 10µm in length.
USA: NIOSH: TWA	5 mg/m ³ Fiber glas®, Fiberglass, Glass fibers, Glass wool, total dust		
471-34-1	Calcium carbonate	Canada, Alberta: OEL 8 hour	10 mg/m ³
		Canada, BC: OEL STEL	20 mg/m ³ (Calcium carbonate incl. Limestone, Marble)
		Canada, BC: OEL TWA	10 mg/m ³ (Calcium carbonate incl. Limestone, Marble)
		Canada, Québec: VEMP	10 mg/m ³ (inhalable fraction)
		USA: NIOSH: TWA	10 mg/m ³ (inhalable fraction)
13983-17-0	Wollastonite	USA: NIOSH: TWA	5 mg/m ³ (respirable fraction)
		USA: OSHA: TWA	15 mg/m ³ (inhalable fraction)
		USA: OSHA: TWA	5 mg/m ³ (respirable fraction)
		Canada, Québec: VEMP	10 mg/m ³ (inhalable fraction)
		Canada, Québec: VEMP	5 mg/m ³ (respirable fraction)

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016
Version: 3

Language: en-CA,US

Date of print: 19/12/2016
Page: 7 of 12

CAS No.	Designation	Type	Limit value
13463-67-7	Titanium dioxide	Canada, Alberta: OEL 8 hour	10 mg/m ³
		Canada, BC: OEL TWA	10 mg/m ³
		Canada, BC: OEL TWA	3 mg/m ³ respirable fraction
		Canada, Québec: VEMP	10 mg/m ³ (inhalable fraction)
		USA: ACGIH: TWA	10 mg/m ³
		USA: OSHA: TWA	15 mg/m ³
7631-86-9	Silicon dioxide	USA: NIOSH: TWA	6 mg/m ³
		USA: OSHA: TWA	20 mppcf
		USA: OSHA: TWA	80 mg/m ³ total dust
26761-40-0	Diisodecylphthalate	Canada, Ontario: OEL TWA	5 mg/m ³
9002-86-2	Polyvinyl chloride	Canada, BC: OEL TWA	1 mg/m ³
		USA: ACGIH: TWA	1 mg/m ³ (respirable fraction)
1309-37-1	Diiron trioxide	Canada, Alberta: OEL 8 hour	5 mg/m ³ (respirable fraction)
		Canada, BC: OEL STEL	10 mg/m ³ Smoke; calculated as Fe
		Canada, BC: OEL TWA	10 mg/m ³ (oxide, red)
		Canada, BC: OEL TWA	3 mg/m ³ (oxide, red) respirable fraction
		Canada, BC: OEL TWA	5 mg/m ³ (oxide dust)
		Canada, BC: OEL TWA	5 mg/m ³ Smoke; calculated as Fe
		Canada, Québec: VEMP	10 mg/m ³ (red)
		Canada, Québec: VEMP	5 mg/m ³
		USA: ACGIH: TWA	5 mg/m ³ (respirable fraction)
		USA: OSHA: TWA	10 mg/m ³ (Iron oxide, fume; calculated as Fe)
		USA: OSHA: TWA	15 mg/m ³ (inhalable fraction, red)
USA: OSHA: TWA	5 mg/m ³ (red, respirable fraction)		
14808-60-7	Quartz (SiO ₂)	Canada, Alberta: OEL 8 hour	0.025 mg/m ³
		Canada, BC: OEL TWA	0.025 mg/m ³
		Canada, Ontario: OEL TWA	0.1 mg/m ³ (respirable fraction)
		Canada, Québec: VEMP	0.1 mg/m ³ (respirable fraction)
		USA: ACGIH: TWA	0.025 mg/m ³ (respirable fraction)
		USA: NIOSH: TWA	0.05 mg/m ³ (respirable fraction)
		USA: OSHA: TWA	10 mg/m ³ /% SiO ₂ + 2 (respirable Dust)
		USA: OSHA: TWA	250 mppcf/%SiO ₂ +5 fine dust
		USA: OSHA: TWA	30 mg/m ³ /% SiO ₂ + 2 inhalable fraction

Engineering controls

In the case of the formation of dust: Provide good ventilation and/or an exhaust system in the work area. If not available, use respiratory protection.
See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection For mechanical processing: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection For mechanical processing: Wear suitable protective clothing and shoes.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016
Version: 3

Language: en-CA,US

Date of print: 19/12/2016
Page: 8 of 12

For mechanical processing: Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Respiratory protection: In case of dust formation:
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General hygiene considerations:

For mechanical processing: Do not inhale substance. Avoid contact with skin and eyes. When using do not eat, drink or smoke. Change contaminated clothing. Wash hands before breaks and after work. Work place should be equipped with a shower and an eye rinsing apparatus.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: solid Color: varying colors
Odor:	No data available
Odor threshold:	No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	No data available
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Additional information:	No data available

10. Stability and reactivity

Reactivity:	no data available
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	No hazardous reaction when handled and stored according to provisions.
Conditions to avoid:	Protect from heat and direct sunlight.
Incompatible materials:	Oxidizing agents, acids.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016

Version: 3

Language: en-CA,US

Date of print: 19/12/2016

Page: 9 of 12

Hazardous decomposition products:

At temperatures above 482 °F (250 °C) hazardous decomposition products may be generated.

Thermal decomposition: No data available

11. Toxicological information

Toxicological tests

Toxicological effects: Acute toxicity (oral): Lack of data.
Acute toxicity (dermal): Lack of data.
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Lack of data.
Eye damage/irritation: Lack of data.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Lack of data.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: Chronic toxicity carcinogenic effect:
Information about Quartz (SiO₂):
IARC Rating: Group 1
OSHA Carcinogen: not listed
NTP Rating: listed
Information about silicon dioxide:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Information about Wollastonite:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Information about Titanium dioxide:
IARC Rating: Group 2B
OSHA Carcinogen: not listed
NTP Rating: not listed
Information about Diiron trioxide:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

Symptoms

In case of inhalation: Inhalation of dust may cause irritation of the respiratory system.
Irritation of nose, throat, lung.

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016

Version: 3

Language: en-CA,US

Date of print: 19/12/2016

Page: 10 of 12

12. Ecological information

Ecotoxicity

Further details: No data available

Mobility in soil

No data available

Persistence and degradability

Further details: No data available

Additional ecological information

General information: Do not allow to enter into ground-water, surface water or drains.

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Packing can be recycled or disposed of.

14. Transport information

USA: Department of Transportation (DOT)

Proper shipping name: Not restricted

Canada: Transportation of Dangerous Goods (TDG)

Shipping name: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - Canada

No data available

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016

Version: 3

Language: en-CA,US

Date of print: 19/12/2016

Page: 11 of 12

National regulations - U.S. Federal Regulations

Product:	This product is an article as defined by TSCA regulations, and is exempt from TSCA inventory listing requirements.
Aluminium oxide:	Other Environmental Laws: SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard NIOSH Recommendations: Occupational Health Guideline: 0021
Silicon carbide:	NIOSH Recommendations: Occupational Health Guideline: 0555
Wollastonite:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed
Titanium dioxide:	Carcinogen Status: IARC Rating: Group 2B OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0617
Silicon dioxide:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0552
Polyvinyl chloride:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed
Diiiron trioxide:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0344
Quartz (SiO ₂):	Carcinogen Status: IARC Rating: Group 1 OSHA Carcinogen: not listed NTP Rating: listed NIOSH Recommendations: Occupational Health Guideline: 0553

SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010



Non-Woven Abrasives

Product number 014

Revision date: 14/12/2016
Version: 3

Language: en-CA,US

Date of print: 19/12/2016
Page: 12 of 12

National regulations - U.S. State Regulations

Aluminium oxide:	Delaware Air Quality Management List: DRQ: 100 - RQ State: State requirement differs from Federal Massachusetts Haz. Substance codes: F9 Minnesota Haz. Substance: Codes: A - Ratings: 10.16 - Status: Title III. TRI. New Jersey RTK Hazardous Substance: DOT: - - Sub No.: 2891 - TPQ: - Pennsylvania Haz. Substance code: E Washington Air Contaminant: TWA: 10 mg
Titanium dioxide:	California Proposition 65: cancer Rhode Island HSL: listed
Diisodecylphthalate:	California Proposition 65: developmental Rhode Island HSL: listed
Diiron trioxide:	Idaho Air Pollutant List: Title 585 -- AAC: 0.25 -- EL: 0.333 -- WEL: 5 Title 586 - Massachusetts Haz. Substance codes: 2 Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 5 mg
Quartz (SiO ₂):	California Proposition 65: cancer Rhode Island HSL: listed

16. Other information

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)
Fire: 0 (Minimal)
Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)
Flammability: 0 (Minimal)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
	X

Reason of change: Changes in section 1: emergency phone number
Date of first version: 21/12/2015

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products.

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 1 de 13

1. Identification de la substance ou préparation et de la société productrice

Identificateur de produit

Nom commercial du produit:

Non-Woven Abrasives
Cette fiche de données de sécurité est valable pour les produits suivants:
POLINOX® unmounted flap wheels
POLINOX® cross buffs
POLINOX® mounted flap wheels
POLINOX® unitized wheels
POLINOX® unitized discs
POLINOX® convolute wheels
POLINOX® spindle mount discs
POLINOX® hand pads
POLINOX® marbling discs
POLINOX® finishing drums
POLIVLIES® surface conditioning belts
POLIVLIES® surface conditioning hook & loop discs
POLIVLIES® flap disc
POLICLEAN® discs
POLICLEAN® mounted wheels
COMBIDISC® POLICLEAN® discs
COMBIDISC® surface conditioning discs
COMBIDISC® finishing discs
COMBIDISC® unitized discs
COMBICLICK® surface conditioning discs
COMBICLICK® finishing discs
COMBICLICK® unitized discs
Non Woven Shop Rolls

Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées

Utilisation générale: Meulage et ponçage de différents types de matériaux.
Uniquement pour usages industriels

Renseignements concernant le fournisseur de la fiche de données de sécurité

Nom de la société:

PFERD INC.
Rue/B.P.: 9201 W. Heather Ave.
Place, Lieu: Milwaukee, WI 53224,
USA
WWW: www.pferdusa.com
E-mail: sales@pferdusa.com
Téléphone: 262-509-5614
Télécopie: 262-255-2840
Service responsable de l'information: 1-800-342-9015

PFERD CANADA INC.
Rue/B.P.: 5570 McAdam Road
Place, Lieu: Mississauga, Ontario L4Z 1P1, Canada
WWW: www.pferdusa.com
E-mail: sales@pferdcanada.ca
Téléphone: (905) 501-1555
Télécopie: (905) 501-1554
Service responsable de l'information: 1-866-245-1555

Numéro d'appel d'urgence

USA/Canada: 1-800-255-3924

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 2 de 13

2. Identification des dangers

Aperçu de cas d'urgence

Aspect: Forme: solide
 Couleur: différentes couleurs
Odeur: Aucune donnée disponible
Classification: Produit non soumis à la classification et au marquage de risque.

Statut des risques

Ce produit est classé comme non dangereux sous les lois de l'OSHA aux États-Unis et du SIMDUT au Canada.

Dangers non classés ailleurs

Des particules et des poussières peuvent être générées lors de l'usinage ultérieur.
L'inhalation de poussière peut causer une irritation des voies respiratoires.
Fibres et poussières: Irritation cutanée, irritation des muqueuses, irritations oculaires.
voir section 11: Informations toxicologiques

3. Composition / Informations sur les composants

Spécification chimique: Non-woven abrasives

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 3 de 13

Composants pertinents:

n°CAS	Désignation	Teneur	Classification
CAS -	Nylon fibre	< 80 %	néant
CAS 1344-28-1	Oxyde d'aluminium	< 70 %	néant
CAS 409-21-2	Carbure de silicium	< 70 %	néant
CAS -	résine synthétique, polymérisé	< 60 %	néant
CAS -	Cotton-Polyester-cloth	< 40 %	néant
CAS -	Polyester cloth	< 40 %	néant
CAS -	Cotton cloth	< 40 %	néant
CAS 65997-17-3	Fibre glass weaves	< 30 %	néant
CAS 471-34-1	Carbonate de calcium	< 5 %	néant
CAS 13983-17-0	Wollastonite	< 5 %	néant
CAS -	Aluminium Silicates	< 5 %	néant
CAS 13463-67-7	Dioxyde de titane	< 3 %	Carc. 2.
CAS 7631-86-9	Dioxyde de silice	< 2 %	néant
CAS -	Papier	< 2 %	néant
CAS 26761-40-0	Diisodecylphthalate	< 1.5 %	néant
CAS 9002-86-2	Chlorure de polyvinyle	< 1.5 %	néant
CAS 1309-37-1	Trioxyde de difer	< 1.5 %	néant
CAS 8042-47-5	Huile minérale blanche (pétrole)	< 1 %	néant
CAS -	Pigments	< 1 %	néant
CAS 64742-52-5	Distillats naphténiques lourds (pétrole), hydrotraités	< 0.2 %	néant
CAS 14808-60-7	Quartz (SiO ₂)	< 0.15 %	Carc. 1A.

Indications complémentaires:

Les ingrédients sont alliés au produit.

4. Premiers secours

En cas d'inhalation: Fibres/poussières: Veiller à un apport d'air frais. En cas de malaise, consulter un médecin.

Après contact avec la peau:

Fibres/poussières: Laver les parties contaminées avec de l'eau et du savon. En cas de malaises, consulter un médecin.

Contact avec les yeux:

Fibres/poussières: Rincer l'oeil aussitôt en tenant les paupières ouvertes pendant 10 à 15 minutes sous l'eau courante. Le cas échéant, retirer les lentilles de contact. En cas d'irritation oculaire, consulter un ophtamologue.

Ingestion:

Fibres/poussières: Rincer la bouche avec de l'eau. Faire boire de l'eau par petites gorgées. En cas de malaise, consulter un médecin.

Principaux symptômes et effets, aigus et différés

Fibres/poussières: Risque d'irritation de la peau, des yeux et des voies respiratoires.

Informations pour le médecin

Traitement symptomatique.

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 4 de 13

5. Mesures de lutte contre l'incendie

Point éclair/plage d'inflammabilité:

Aucune donnée disponible

Température d'auto-inflammabilité:

Aucune donnée disponible

Agents d'extinction appropriés::

Le produit est ininflammable. Les moyens d'extinction seront donc choisis en fonction de l'environnement.

Dangers particuliers résultant de la substance ou du mélange

A des températures supérieures à 482 °F (250 °C), des produits de décomposition dangereux peuvent se former.

Équipement spécial de protection en cas d'incendie:

Utiliser un appareil respiratoire autonome et des vêtements ignifugés.

Indications complémentaires:

Éviter la pénétration des eaux d'extinction dans les eaux superficielles ou la nappe phréatique.

6. Mesures à prendre en cas de dispersion accidentelle

Mesures de précautions individuelles:

Éviter la formation de poussière. Ne pas inhaler la substance.
Lors du chauffage: risque de dégagement de gazes ou de vapeurs.
Assurer une aération suffisante. Porter un équipement de protection approprié.
Éviter le contact avec la substance. Tenir toute personne non protégée à l'écart.

Précautions en matière d'environnement:

Éviter une infiltration dans le sol, les plans et voies d'eau et les canalisations.

Méthodes de nettoyage: Absorber mécaniquement et mettre dans des récipients adéquats en vue de l'élimination.

7. Manipulation et stockage

Manipulation

Précautions de manipulation:

Assurer une bonne aération et ventilation de l'entrepôt et du poste de travail. Éviter la formation de poussière.
Lors du chauffage: risque de dégagement de gazes ou de vapeurs.
Ne pas inhaler la substance. Porter un équipement de protection approprié. Éviter le contact avec la substance.

Stockage

Conditions de stockage et de conditionnement:

Conserver le récipient bien fermé et à l'abri de l'humidité.
Protéger de la chaleur et des radiations solaires directes.

Conseils pour le stockage en commun:

Ne pas stocker avec agents oxydants ou acides.
Ne pas stocker avec des produits alimentaires.

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 5 de 13

8. Contrôle de l'exposition/ protection individuelle

Directives de l'exposition

Valeurs limites au poste de travail:

N°CAS	Désignation	Type	Valeur seuil
1344-28-1	Oxyde d'aluminium	Canada, Alberta: OEL 8 hour	10 mg/m ³
		Canada, Québec: VEMP	10 mg/m ³ (fraction inhalable)
		EUA: OSHA: TWA	15 mg/m ³ fraction inhalable
		EUA: OSHA: TWA	5 mg/m ³ (fraction respirable)
409-21-2	Carbure de silicium	Canada, Alberta: OEL 8 hour	0.1 fibres/cm ³ (fibrous, including whiskers; fraction inhalable)
		Canada, Alberta: OEL 8 hour	10 mg/m ³ (non-fibrous; fraction inhalable)
		Canada, Alberta: OEL 8 hour	3 mg/m ³ (non-fibrous; fraction respirable)
		Canada, BC: OEL TWA	0.1 fibres/cm ³ (fibrous, including whiskers)
		Canada, BC: OEL TWA	10 mg/m ³ (non-fibrous; fraction inhalable)
		Canada, BC: OEL TWA	3 mg/m ³ (non-fibrous; fraction respirable)
		Canada, Ontario: OEL TWA	0.1 fibres/cm ³ (fibrous, including whiskers; fraction inhalable)
		Canada, Ontario: OEL TWA	10 mg/m ³ (non-fibrous; fraction inhalable)
		Canada, Ontario: OEL TWA	3 mg/m ³ (non-fibrous; fraction respirable)
		Canada, Québec: VEMP	10 mg/m ³ (non-fibrous; fraction inhalable)
		EUA: ACGIH: TWA	0.1 fibres/cm ³ (fibrous, including whiskers)
		EUA: ACGIH: TWA	10 mg/m ³ (fraction inhalable; particulate matter containing no asbestos and < 1% crystalline silica)
		EUA: ACGIH: TWA	3 mg/m ³ (fraction respirable; particulate matter containing no asbestos and < 1% crystalline silica)
		EUA: NIOSH: TWA	10 mg/m ³ fraction inhalable
EUA: NIOSH: TWA	5 mg/m ³ (fraction respirable)		
EUA: OSHA: TWA	15 mg/m ³ fraction inhalable		
EUA: OSHA: TWA	5 mg/m ³ (fraction respirable)		

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 6 de 13

N°CAS	Désignation	Type	Valeur seuil
65997-17-3	Fibre glass weaves	Canada, Alberta: OEL 8 hour	1 fibres/cm ³
		Canada, Alberta: OEL 8 hour	Glass Fibres, Continuous filament 5 mg/m ³
		Canada, BC: OEL TWA	Glass Fibres, continuous filament, glass wool, fraction inhalable 1 fibres/cm ³
		Canada, BC: OEL TWA	Synthetic Vitreous Fibres - Continuous filament glass fibres 5 mg/m ³
		Canada, Ontario: OEL TWA	Synthetic Vitreous Fibres - Continuous filament glass fibres; fraction inhalable 1 fibres/cm ³
		Canada, Ontario: OEL TWA	Synthetic Vitreous Fibres, Continuous filament glass fibres 5 mg/m ³
		Canada, Québec: VEMP	Synthetic Vitreous Fibres (Man Made Mineral Fibres), Continuous filament glass fibres 10 mg/m ³
		EUA: ACGIH: TWA	Fibre de verre en filament continu; Pt note 1 1 fibres/cm ³
		EUA: ACGIH: TWA	Synthetic vitreous fibres, Continuous filament glass fibres 5 mg/m ³
		EUA: NIOSH: TWA	Synthetic vitreous fibres, Continuous filament glass fibres; fraction inhalable 3 fibres/cm ³
EUA: NIOSH: TWA	Fibers less than or equal to 3,5 µm in diameter and greater than or equal to 10µm in length. 5 mg/m ³		
471-34-1	Carbonate de calcium	Canada, Alberta: OEL 8 hour	10 mg/m ³
		Canada, BC: OEL STEL	20 mg/m ³
		Canada, BC: OEL TWA	(Calcium carbonate incl. Limestone, Marble) 10 mg/m ³
		Canada, Québec: VEMP	(Calcium carbonate incl. Limestone, Marble) 10 mg/m ³ (fraction inhalable)
		EUA: NIOSH: TWA	10 mg/m ³ (fraction inhalable)
		EUA: OSHA: TWA	5 mg/m ³ (fraction respirable)
EUA: OSHA: TWA	15 mg/m ³ (fraction inhalable)		
EUA: OSHA: TWA	5 mg/m ³ (fraction respirable)		

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 7 de 13

N°CAS	Désignation	Type	Valeur seuil
13983-17-0	Wollastonite	Canada, Québec: VEMP Canada, Québec: VEMP	10 mg/m ³ (fraction inhalable) 5 mg/m ³ (fraction respirable)
13463-67-7	Dioxyde de titane	Canada, Alberta: OEL 8 hour Canada, BC: OEL TWA Canada, BC: OEL TWA Canada, Québec: VEMP EUA: ACGIH: TWA EUA: OSHA: TWA	10 mg/m ³ 10 mg/m ³ 3 mg/m ³ fraction respirable 10 mg/m ³ (fraction inhalable) 10 mg/m ³ 15 mg/m ³
7631-86-9	Dioxyde de silice	EUA: NIOSH: TWA EUA: OSHA: TWA EUA: OSHA: TWA	6 mg/m ³ 20 mppcf 80 mg/m ³ poussière globale
26761-40-0	Diisodecylphthalate	Canada, Ontario: OEL TWA	5 mg/m ³
9002-86-2	Chlorure de polyvinyle	Canada, BC: OEL TWA EUA: ACGIH: TWA	1 mg/m ³ 1 mg/m ³ (fraction respirable)
1309-37-1	Trioxyde de difer	Canada, Alberta: OEL 8 hour Canada, BC: OEL STEL Canada, BC: OEL TWA Canada, BC: OEL TWA Canada, BC: OEL TWA Canada, BC: OEL TWA Canada, Québec: VEMP Canada, Québec: VEMP EUA: ACGIH: TWA EUA: OSHA: TWA EUA: OSHA: TWA EUA: OSHA: TWA	5 mg/m ³ (fraction respirable) 10 mg/m ³ Fumée; exprimé en Fe 10 mg/m ³ (oxide, rouge) 3 mg/m ³ (oxide, rouge) fraction respirable 5 mg/m ³ (oxide dust) 5 mg/m ³ Fumée; exprimé en Fe 10 mg/m ³ (rouge) 5 mg/m ³ 5 mg/m ³ (fraction respirable) 10 mg/m ³ (Iron oxide, fume; exprimé en Fe) 15 mg/m ³ (fraction inhalable, rouge) 5 mg/m ³ (rouge, fraction respirable)
14808-60-7	Quartz (SiO ₂)	Canada, Alberta: OEL 8 hour Canada, BC: OEL TWA Canada, Ontario: OEL TWA Canada, Québec: VEMP EUA: ACGIH: TWA EUA: NIOSH: TWA EUA: OSHA: TWA EUA: OSHA: TWA EUA: OSHA: TWA	0.025 mg/m ³ 0.025 mg/m ³ 0.1 mg/m ³ (fraction respirable) 0.1 mg/m ³ (fraction respirable) 0.025 mg/m ³ (fraction respirable) 0.05 mg/m ³ (fraction respirable) 10 mg/m ³ /% SiO ₂ + 2 (respirable Dust) 250 mppcf/%SiO ₂ +5 poussière fine 30 mg/m ³ /% SiO ₂ + 2 fraction inhalable

Contrôle de l'exposition

En cas de dégagement de poussière: Assurer une bonne ventilation de l'atelier et/ou mettre en place un système d'aspiration de l'air au poste de travail.

Se reporter également aux informations du chapitre 7, paragraphe stockage.

Protection individuelle

Protection yeux/visage En cas de traitement mécanique: Lunettes de protection hermétiques conformes à la norme OSHA Standard - 29 CFR: 1910.133 o ANSI Z87.1-2010.

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 8 de 13

Protection de la peau	En cas de traitement mécanique: Pendant la manipulation, porter un vêtement de protection et des chaussures appropriés. En cas de traitement mécanique: Gants de protection conforme à la OSHA Standard - 29 CFR: 1910.138.
Protection respiratoire:	En cas de dégagement de poussière: La classe des filtres de protection respiratoire doit absolument être adaptée à la concentration max. du polluant (gaz/vapeur/aérosol/particules) pouvant être produit. En cas de dépassement, il faut utiliser des appareils indépendants!
Mesures générales de protection et d'hygiène:	En cas de traitement mécanique: Ne pas inhaler la substance. Éviter le contact avec la peau et les yeux. Ne pas manger, ne pas boire et ne pas fumer pendant l'utilisation. Changer les vêtements imprégnés. Se laver les mains avant les pauses et à la fin du travail. Equiper les lieux de travail d'un rince-œil et d'une douche de premier secours.

9. Propriétés physiques et chimiques

Informations sur les propriétés physiques et chimiques essentielles

Aspect:	Forme: solide Couleur: différentes couleurs
Odeur:	Aucune donnée disponible
Seuil olfactif:	Aucune donnée disponible
Valeur pH:	Aucune donnée disponible
Point de fusion/point de congélation:	Aucune donnée disponible
Point initial d'ébullition et intervalle d'ébullition:	Aucune donnée disponible
Point éclair/plage d'inflammabilité:	Aucune donnée disponible
Vitesse d'évaporation:	Aucune donnée disponible
Inflammabilité:	Aucune donnée disponible
Limites d'explosibilité:	Aucune donnée disponible
Tension de vapeur:	Aucune donnée disponible
Densité de la vapeur:	Aucune donnée disponible
Densité:	Aucune donnée disponible
Solubilité:	Aucune donnée disponible
Coefficient de partage: n-octanol/eau:	Aucune donnée disponible
Température d'auto-inflammabilité:	Aucune donnée disponible
Décomposition thermique:	Aucune donnée disponible
Indications diverses:	Aucune donnée disponible

10. Stabilité et réactivité

Réactivité:	aucune donnée disponible
Stabilité chimique:	Stable si stocké dans les conditions prévues.

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 9 de 13

Possibilité de réactions dangereuses

Des réactions dangereuses ne se produisent pas si utilisé et stocké correctement.

Conditions à éviter: Protéger de la chaleur et des radiations solaires directes.

Matières incompatibles: Agents oxydants, acides.

Produits de décomposition dangereux:

A des températures supérieures à 482 °F (250 °C), des produits de décomposition dangereux peuvent se former.

Décomposition thermique: Aucune donnée disponible

11. Informations toxicologiques

Tests toxicologiques

Effets toxicologiques: Toxicité aiguë (par voie orale): Manque de données.
Toxicité aiguë (dermique): Manque de données.
Toxicité aiguë (par inhalation): Manque de données.
Corrosion cutanée/irritation cutanée: Manque de données.
Endommagement/irritation des yeux: Manque de données.
Sensibilisation respiratoire: Manque de données.
Sensibilisation cutanée: Manque de données.
Mutagénicité sur les cellules germinales/Génotoxicité: Manque de données.
Cancerogénité: Manque de données.
Toxicité pour la reproduction: Manque de données.
Effets sur et par le lait maternel: Manque de données.
Toxicité spécifique pour certains organes cibles (exposition unique): Manque de données.
Toxicité spécifique pour certains organes cibles (exposition répétée): Manque de données.
Danger par aspiration: Manque de données.

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 10 de 13

Autres informations: Toxicité chronique effet cancérigène:
Indication sur Quartz (SiO₂):
IARC Rating: Group 1
OSHA Carcinogen: not listed
NTP Rating: listed
Indication sur dioxyde de silice:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Indication sur Wollastonite:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Indication sur Dioxyde de titane:
IARC Rating: Group 2B
OSHA Carcinogen: not listed
NTP Rating: not listed
Indication sur Trioxyde de difer:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

Symptômes

En cas d'inhalation:
L'inhalation de poussière peut causer une irritation des voies respiratoires.
Irritation nez, pharynx, poumon.

12. Données écologiques

Écotoxicité

Indications diverses: Aucune donnée disponible

Mobilité dans le sol

Aucune donnée disponible

Persistance et dégradabilité

Indications diverses: Aucune donnée disponible

Indications diverses relatives à l'écologie

Remarques générales: Ne pas laisser pénétrer dans la nappe phréatique, les plans d'eau ou les canalisations.

13. Considérations relatives à l'élimination

Produit

Recommandation: L'élimination doit se faire selon les prescriptions des autorités locales.

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 11 de 13

Conditionnement

Recommandation: L'élimination doit se faire selon les prescriptions des autorités locales. Les emballages peuvent être revalorisés ou recyclés.

14. Informations relatives au transport

USA: Department of Transportation (DOT)

Désignation technique spécifique: Non réglementé

Canada: Transportation of Dangerous Goods (TDG)

Shipping name: Non réglementé

Transport maritime (IMDG)

Désignation technique spécifique: Non réglementé

Polluant marin: non

Transport aérien (IATA)

Désignation technique spécifique: Non réglementé

Indications diverses

Le produit n'est pas un produit dangereux selon les règlements applicables au transport.

15. Règlements

Directives nationales - Canada

Aucune donnée disponible

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 12 de 13

Directives nationales - U.S. Federal Regulations

Produit:	Ce produit est un article tel que défini par les règlements de la Loi TSCA et est donc exempt des exigences de l'inventaire TSCA.
Oxyde d'aluminium:	Other Environmental Laws: SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard NIOSH Recommendations: Occupational Health Guideline: 0021
Carbure de silicium:	NIOSH Recommendations: Occupational Health Guideline: 0555
Wollastonite:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed
Dioxyde de titane:	Carcinogen Status: IARC Rating: Group 2B OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0617
Dioxyde de silice:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0552
Chlorure de polyvinyle:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed
Trioxyde de difer:	Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0344
Quartz (SiO ₂):	Carcinogen Status: IARC Rating: Group 1 OSHA Carcinogen: not listed NTP Rating: listed NIOSH Recommendations: Occupational Health Guideline: 0553

FICHE DE DONNÉES DE SÉCURITÉ

conforme WHMIS 2015 et ANSI Z400.1-2010



Non-Woven Abrasives

Numéro du produit 014

Mise à jour: 14/12/2016
Version: 3

Langue: fr-CA,US

Date d'édition: 19/12/2016
Page: 13 de 13

Directives nationales - U.S. State Regulations

Oxyde d'aluminium:	Delaware Air Quality Management List: DRQ: 100 - RQ State: State requirement differs from Federal Massachusetts Haz. Substance codes: F9 Minnesota Haz. Substance: Codes: A - Ratings: 10.16 - Status: Title III. TRI. New Jersey RTK Hazardous Substance: DOT: - - Sub No.: 2891 - TPQ: - Pennsylvania Haz. Substance code: E Washington Air Contaminant: TWA: 10 mg
Dioxyde de titane:	California Proposition 65: cancer Rhode Island HSL: listed
Diisodecylphthalate:	California Proposition 65: developmental Rhode Island HSL: listed
Trioxyde de difer:	Idaho Air Pollutant List: Title 585 -- AAC: 0.25 -- EL: 0.333 -- WEL: 5 Title 586 - Massachusetts Haz. Substance codes: 2 Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 5 mg
Quartz (SiO ₂):	California Proposition 65: cancer Rhode Island HSL: listed

16. Autres informations

Systèmes d'évaluation de danger:



NFPA Hazard Rating:
Health: 1 (Slight)
Fire: 0 (Minimal)
Reactivity: 0 (Minimal)

HMIS Version III Rating:
Health: 1 (Slight)
Flammability: 0 (Minimal)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
	X

Raison des dernières modifications:

Modification dans la section 1: Numéro de téléphone d'appel d'urgence

Créée: 21/12/2015

Service responsable de la fiche technique

Responsable: voir section 1: Service responsable de l'information

Les informations figurant dans cette fiche de données de sécurité correspondent à nos connaissances actuelles au moment de l'impression. Ces informations visent à fournir des points de repère pour une manipulation sûre du produit objet de cette fiche de données de sécurité, concernant en particulier son stockage, sa mise en oeuvre, son transport et son élimination. Les indications ne sont pas applicables à d'autres produits.